

IN THE SPECIFICATION:

The specification as amended below with replacement paragraphs shows added text with underlining and deleted text with ~~striketrough~~.

Please REPLACE Paragraph 29 on page 6 with the following paragraph:

As shown in FIGS. 4 through 6B, the tray 40 comprises a stationary tray 42 having a first profile groove portion 46a provided in a lower section along a lengthwise direction thereof, and a rotatable tray 44 having a second profile groove portion 46b opposite to the first profile groove portion 46a of the stationary tray 42, such that the stationary tray 42 and the rotatable tray 44 are combined to each other to form a box shape with the top opening. The first and second groove portions combine to form a profile groove 46. One or more profiles 50, 51 are compressively fit into a space formed by the first and second profile groove portions 46a and 46b of the stationary and rotatable trays 42 and 44.

Please REPLACE Paragraph 32 bridging pages 6 and 7 with the following paragraph:

The respective first and second profile groove portions 46a and 46b of the stationary and rotatable trays 42 and 44, each have a rectangular cross-section, and are provided with a plurality of breakaway-prevention protrusions 47 securely and compressively supporting partial outer surfaces of the profiles 50, 51 so as to prevent the profiles 50, 51 corresponding to the first and second profile groove portions 46a and 46b from breaking away therefrom.

Please REPLACE Paragraph 33 on page 7 with the following paragraph:

The breakaway-prevention protrusions 47 are incorporated with the respective stationary and rotatable trays 42 and 44 by molding, and are plurally provided in inner upper and inner lower edges of each of the first and second profile groove portions 46a and 46b. However, the breakaway-prevention protrusions 47 may vary in a placing position, a number, a size, and a shape thereof as necessary within ranges to securely and compressively support each of the profiles 50, 51.